MiLES

a tool for every hand...™



FASTENING TOOLS

www.milesincorporation.com

a product from kangaro

COMPANY PROFILE

Mission

Our mission spells our ambition to have every user of our line of products in the world to hold our tool and say I ENJOY MILES TOOL. We want to see end users satisfied for the money that they pay and the quality that they get, as it is an automatic WIN-WIN for MILES, for all its chain partners and most importantly the end users.

About Us

Kangaro group which inter - alia includes Kangaro Industries (Regd.), Kanin (India), Kangaro Industries Limited & Munix (India) Pvt. Ltd. Are well known manufacturers & exporters of various products such as Staplers, Staples, Staple Removers, Paper Punches, Scissors, Carbon Papers, Stitching wire, Gun Tackers, Pneumatic Tools and Industrial Staples.

Infrastructure

Our manufacturing facility houses a comprehensive sheet metal components manufacturing shop, a machine shop having a range of special purpose machines, fully automatic electroplating plant, fully automatic powder coating plant, plastic injection moulding shop besides all other required facilities in-house. We have fully automatic wire drawing lines to manufacture desired quality of wire used to manufacture staples on completely automatic multiple wire staple manufacturing lines. All Units are vertically integrated, wherein all manufacturing operations are performed in-house, right from manufacturing of smallest part, spring, rivet etc. to complex multi-part components. This helps to maintain required and desired quality consistently.

R&D Section & Tool Room

Facility has a well equipped Research and Development Centre and an ultra modern Tool Room having all latest facilities CAD/ CAM using the latest software, CNC wire cuts, CNC EDM machines, CNC Milling Machines besides other latest machinery and equipment required to develop quality Tools, Jigs and Fixtures which enable the setup to manufacture the required international quality of its end products.

Quality Policy

'Quality Culture' runs into every segment of Factory's working supported by a team of more than 3000 highly qualified professionals, engineers, technocrats and dedicated workers, whose devotion and dedication have become milestones of MILE's success. "Company believes that quality is the life line of every business and is committed to satisfy its customers by manufacturing and supplying its products to their entire satisfaction first time and every time with continual up gradation in the effectiveness of the quality management system."

Market Presence

Kangaro Group has grown manifold in last five decades making KANGARO, MUNIX and MILES most trusted brands. Supported by an efficient distribution network and a dynamic sales team. We are the largest manufacturer & exporter not only in india but in entire south-East Asia and export goods to more than 100 countries that cover Middle East, Africa, South Asia, Far East, United States, Central and Southern America, South Africa, Europe etc. and are now expanding our portfolio under MILES brand.

We take this opportunity to present complete range of our products under MILES with detailed specification.

TP 10

Features
- Light weight high impact ABS plastic body with quality steel components
- Compact design with no loose parts
- Easy drop in loading with reload indicator
- Handle lock for easy storage

Used for
- Cupboards, Fabrics, Iron boards, Decorative work, Upholstery etc.

24 Series	Outer Crown	12.80mm
	Inner Crown	11.90mm
	Thickness	0.35 x 0.70mm
	Leg Length	6~8mm
23 Series	Outer Crown	13.00mm
	Inner Crown	11.60mm
	Thickness	0.60 x 0.75mm
	Leg Length	6~24mm
T Series	Outer Crown	12.75mm
	Inner Crown	11.60mm
	Thickness	0.51 x 0.70mm
	Leg Length	8~13mm

Tools Specifications

Staple Use	: 24/6, 23 Series, T-8, T-10
Leg Length	: 6 ~ 10mm

TS 13H

Features
- All metal robust construction
- Sleek design with no loose parts
- Easy drop in loading with reload indicator
- Handle lock for easy storage
- Elegant soft rubber grip for extra working comfort

Used for
- Textile, Upholstery, Wall Decorating Beading, Canvas etc.

23 Series	Outer Crown	13.00mm
	Inner Crown	11.60mm
	Thickness	0.60 x 0.75mm
	Leg Length	6~24mm
T Series	Outer Crown	12.75mm
	Inner Crown	11.60mm
	Thickness	0.51 x 0.70mm
	Leg Length	8~13mm

Tools Specifications

Staple Use	: 23 Series, T-8, T-10, T-13
Leg Length	: 6 ~ 13mm

TS 623

Features
- All metal robust construction
- Compact design with no loose parts
- Easy drop in loading with reload indicator
- Handle lock for easy storage
- Ergonomic handle with soft rubber grip for extra working comfort

Used for
- Textile, Canvas, Leather, Iron Boards & Upholstery etc.

23 Series	Outer Crown	13.00mm
	Inner Crown	11.60mm
	Thickness	0.60 x 0.75mm
	Leg Length	6~24mm
T Series	Outer Crown	12.75mm
	Inner Crown	11.60mm
	Thickness	0.51 x 0.70mm
	Leg Length	8~13mm

Tools Specifications

Staple Use	: 23 Series, T-8, T-10
Leg Length	: 6 ~ 10mm

TS 2380A

Features
- All metal robust construction
- Sleek design with no loose parts
- With force adjustment
- Easy drop in loading with reload indicator
- Handle lock for easy storage
- Elegant soft rubber grip for extra working comfort

Used for
- Upholstery, Cupboards, Iron boards, Canvas & Frame etc.

23 Series	Outer Crown	13.00mm
	Inner Crown	11.60mm
	Thickness	0.60 x 0.75mm
	Leg Length	6~24mm
No. 80	Outer Crown	12.80mm
	Inner Crown	11.50mm
	Thickness	0.60 x 0.90mm
	Leg Length	3~16mm

Tools Specifications

Staple Use	: 23 Series, No.80
Leg Length	: 6 ~ 13mm

TS 2313A

Features
- All metal robust construction
- Sleek design with no loose parts
- With force adjustment
- Handle lock for easy storage
- Easy drop in loading with reload indicator
- Elegant soft rubber grip for extra working comfort

Used for
- Beading, Frame, Iron boards, Canvas, Upholstery, Leather etc.

18 Gauge

Brads

Head Dia	:	2.00mm
Thickness	:	1.00 x 1.25mm
Leg Length	:	10~50mm

Pins

Thickness	:	1.00 x 1.25mm
Leg Length	:	14mm

23 Series

Outer Crown	:	13.00mm
Inner Crown	:	11.60mm
Thickness	:	0.60 x 0.75mm
Leg Length	:	6~24mm

Tools Specifications

Staple Use	: 23 Series, 18 Gauge (Brads & Pins)
Leg Length	: 6 ~ 13mm (23 Series) : 10~14mm (Brads) : 14mm (Pins)

HT 5800

Hammer Tacker

Features
- All metal robust construction
- Compact design with no loose parts
- Single handed grip for easy operations and to reach odd corners
- Easy drop-in loading with reload indicator
- Elegant soft rubber grip for extra working comfort

Used for
- Fixing Fitted carpets, Insulation, Hang Labels, Posters, Roofing etc.

No. 4

Outer Crown	:	10.50mm
Inner Crown	:	09.40mm
Thickness	:	0.57 x 1.20mm
Leg Length	:	6~14mm

Tools Specifications

Staple Use	: No.4
Leg Length	: 6 ~ 10mm

HT 5850

Hammer Tacker

Features
- All metal robust construction
- Compact design with no loose parts
- Single handed grip for easy operations and to reach odd corners
- Easy drop-in loading with reload indicator
- Elegant soft rubber grip for extra working comfort

Used for
- Fixing Fitted carpets, Insulation, Hang Labels, Posters, Roofing etc.

No. 4

Outer Crown	:	10.50mm
Inner Crown	:	09.40mm
Thickness	:	0.57 x 1.20mm
Leg Length	:	6~14mm

Tools Specifications

Staple Use	: No.4
Leg Length	: 6 ~ 14mm

TP 5540 C

Cable Tacker

Features
- Light Weight high impact ABS plastic body with metal handle
- Compact design with no loose parts
- Easy drop-in loading with reload indicator
- Handle lock for easy storage
- In built wire/cable guide
- Fastens 1/4" round cable & 5/32" flat wire

Used for
- Holiday Lighting, Garlands, Alarm Wire/Cable, Speaker Wire/Cable, Intercom Wire/Cable, TV Wire/ Cable, Computer Wire/Cable & low voltage (max. 50V) Wire/Cable.

Tools Specifications

No.14
Up to 6.5 mm(1/4") Round Wire

No.15
Up to 4.0 mm(5/32") Flat or Round Cable







MS 80-16

Features
- Strong and light weight tool
- Ergonomic handle with rubber grip for extra working comfort
- Long & narrow nose design gets into recesses & corners with unobstructed view
- Special hardened one piece drive blade prolonged life of tool
- Safety trigger reduces the risk of injury

Used for
- Frame, Upholstery, Furniture, Door Trims, Seat Making, Beading, Iron Boards & Canvas etc.



Outer Crown : 12.80mm
Inner Crown : 11.50mm
Thickness : 0.60 x 0.90mm
Leg Length : 3~16mm

Tools Specifications

Staple Use : No.80
Leg Length : 6 ~ 16mm
Working Pressure : 4 ~ 7 Bar

MS 80-16 Pro

Features
- Light weight professional tool
- Reversible driver blade
- Rubber grip for extra working comfort
- Ergonomic design with integarated silencer
- Versatile tool for industry and the craftsman
- Metal Cap reduces vibrations and fatigue

Used for
- Frame, Upholstery, Furniture, Door Trims, Seat Making, Beading, Iron Boards & Canvas etc.



Outer Crown : 12.80mm
Inner Crown : 11.50mm
Thickness : 0.60 x 0.90mm
Leg Length : 3~16mm

Tools Specifications

Staple Use : No.80
Leg Length : 6 ~ 16mm
Working Pressure : 4 ~ 7 Bar

MIE 10J-16 / MS 10J-16

Features
- Design with long & narrow nose for excellent job visibility
- One hand latch for quick reloading
- Bottom loading magazine speeds the loading
- Rubber comfort grip ensures a non slip handling
- Round and plastic head for better push hand grip
- Rear exhaust avoids lubricant from falling onto work surface

Used for
- Furniture, Frame, Upholstery, Beading, Iron Boards & Canvas etc.



Outer Crown : 11.20mm
Inner Crown : 10.00mm
Thickness : 0.60 x 1.20mm
Leg Length : 6~16mm

Tools Specifications

Staple Use : No.10 J
Leg Length : 6 ~ 16mm
Working Pressure : 4 ~ 7 Bar

MI W30-16

Features
- Design with long & narrow nose for excellent job visibility
- One hand latch for quick reloading
- Bottom loading magazine speeds the loading
- Rubber comfort grip ensures a non slip handling
- Round and plastic head for better push hand grip
- Rear exhaust avoids lubricant from falling onto work surface

Used for
- Picture Frame, Upholstery, Furniture, Vehicle Panels, Beading, Iron Boards & Canvas etc.

Outer Crown : 13.00mm
Inner Crown : 11.60mm
Thickness : 0.60 x 0.75mm
Leg Length : 6~24mm

Tools Specifications

Staple Use : 23 Series
Leg Length : 6 ~ 16mm
Working Pressure : 4 ~ 7 Bar

MS 90-25

Features

- Rubber comfort grip ensures a non slip handling and reduce vibration & fatigue
- Light weight & Easy loading
- Touch strike security system
- Multidirectional exhaust cover
- Pro gasket with metal inside
- Special hardened one piece piston set

Used for

- Frame Assembly, Drawer Guide, Panels and Profile boards, Shoe Making, Wooden Cases, Brushes, Frame & Moulding and Decorative etc.

No. 90

Outer Crown	:	05.60mm
Inner Crown	:	03.60mm
Thickness	:	1.00 x 1.25mm
Leg Length	:	9~40mm

Tools Specifications

Staple Use	:	No.90
Leg Length	:	12 ~ 25mm
Working Pressure	:	4 ~ 7 Bar

MI 90-40

Features

- Rubber comfort grip ensures a non slip handling and reduce vibration & fatigue
- Solid & sturdy body
- Long & narrow nose design
- Touch strike security system
- One hand latch for fast reloading
- Multidirectional exhaust cover

Used for

- Frame Assembly, Drawer Guide, Panels and Profile boards, Shoe Making, Wooden Cases, Brushes, Frame & Moulding and Decorative etc.

No. 90

Outer Crown	:	05.60mm
Inner Crown	:	03.60mm
Thickness	:	1.00 x 1.25mm
Leg Length	:	9~40mm

Tools Specifications

Staple Use	:	No.90
Leg Length	:	18 ~ 40mm
Working Pressure	:	4 ~ 7 Bar

MSB 90-40 Combi

Features

- Ergonomic rubber comfort grip ensures a non slip handling
- Light weight & easy loading
- Multidirectional exhaust cover
- Utility belt hook
- Staple viewing slot
- Pro gasket with metal inside
- Special hardened one piece piston set

Used for

- Frame Assembly, Drawer Guide, Panels and Profile boards, Shoe Making, Wooden Cases, Brushes, Frame & Moulding and Decorative etc.

F series

18 Gauge Brads

Head Dia	:	2.00mm
Thickness	:	1.00 x 1.25mm
Leg Length	:	10~50mm

No. 90

Outer Crown	:	05.60mm
Inner Crown	:	03.60mm
Thickness	:	1.00 x 1.25mm
Leg Length	:	9~40mm

Tools Specifications

Staple Use	:	No.90
Leg Length	:	16 ~ 40mm
Brad Use	:	F series (18 gauge)
Leg Length	:	20 ~ 50mm
Working Pressure	:	4 ~ 7 Bar

MS 100-50

Features

- Ergonomic rubber comfort grip ensures a non slip handling
- Solid design & good balance
- Touch strike security system
- Adjustable depth control dial
- Multidirectional exhaust
- Tool less jam clearing mechanism
- Adjustable single fire & bump fire

Used for

- Sheating, Subflooring, Roof Decking, Pallets, Crate and Box Assembly, Vinyl Siding & Frame Assembly etc.

No. 100

Outer Crown	:	10.80mm
Inner Crown	:	07.80mm
Thickness	:	1.40 x 1.60mm
Leg Length	:	25~50mm

Tools Specifications

Staple Use	:	No.100
Leg Length	:	25 ~ 50mm
Working Pressure	:	4 ~ 7 Bar

MI 100-50 Dura

Features
- Rubber comfort grip ensures a non slip handling and reduce vibration & fatigue
- Multidirectional exhaust cover diverts air from the operator
- Bump fire single shot / Contact trip device
- Light and maneuverable anodized aluminum magazines
- Tool-free jam clearing mechanism provides an easy access to the nose if the staple jam
- Depth adjustable knob

Used for
- Sheating, Subflooring, Roof Decking, Pallets, Crate and Box Assembly, Vinyl Siding & Frame Assembly etc.

No. 100

Outer Crown	:	10.80mm
Inner Crown	:	07.80mm
Thickness	:	1.40 x 1.60mm
Leg Length	:	25~50mm

Tools Specifications

Staple Use	:	No.100
Leg Length	:	25 ~ 50mm
Working Pressure	:	4 ~ 7 Bar

MUB 18-32

Features
- Side window to see visible brads for reducing the incidence of dry fire
- Design with slim nose facilitates precise nailing job surface
- Soft rubber grip
- Contact trip device
- Hard coat anodized aluminum loader

Used for
- Cabinet, Windows and Doors, Construction, Wooden Cases, Kite Spindles, Paint Brushes, Modular Kitchen, Frame Assembly & Drawer Guide etc.

F series

18 Gauge Brads

Head Dia	:	2.00mm
Thickness	:	1.00 x 1.25mm
Leg Length	:	10~50mm

Tools Specifications

Brad Use	:	F series (18 gauge)
Leg Length	:	10 ~ 32mm
Working Pressure	:	4 ~ 7 Bar

MI 18-32 Dura

Features
- Light weight & easy loading
- Rubber comfort grip ensures a non slip handling
- Tool less jam clearing mechanism
- Multidirectional exhaust
- Depth control dial to adjust depth of fasteners
- Contact trip device

Used for
- Cabinet, Windows and Doors, Construction, Wooden Cases, Kite Spindles, Paint Brushes, Modular Kitchen, Frame Assembly & Drawer Guide etc.

F series

18 Gauge Brads

Head Dia	:	2.00mm
Thickness	:	1.00 x 1.25mm
Leg Length	:	10~50mm

Tools Specifications

Brad Use	:	F series (18 gauge)
Leg Length	:	10 ~ 32mm
Working Pressure	:	4 ~ 7 Bar

MUB 18-50

Features
- Side window to see visible brads for reducing the incidence of dry fire
- Design with slim nose facilitates precise nailing job surface
- Soft rubber grip
- Contact trip device
- Hard coat anodized aluminum loader

Used for
- Cabinet, Windows and Doors, Construction, Wooden Cases, Kite Spindles, Paint Brushes, Modular Kitchen, Frame Assembly & Drawer Guide etc.

F series

18 Gauge Brads

Head Dia	:	2.00mm
Thickness	:	1.00 x 1.25mm
Leg Length	:	10~50mm

Tools Specifications

Brad Use	:	F series (18 gauge)
Leg Length	:	15 ~ 50mm
Working Pressure	:	4 ~ 7 Bar

MI 18-50 Dura

Features

- Light weight & easy loading
- Multidirectional exhaust
- Tool less jam clearing mechanism
- Depth control dial to adjust depth of fasteners
- Contact trip device
- Rubber comfort grip ensures a non slip handling

Used for

- Cabinet, Windows and Doors, Construction, Wooden Cases, Kite Spindles, Paint Brushes, Modular Kitchen, Frame Assembly & Drawer Guide etc.

F series



Head Dia	:	2.00mm
Thickness	:	1.00 x 1.25mm
Leg Length	:	10~50mm

Tools Specifications

Brad Use	:	F series (18 gauge)
Leg Length	:	15 ~ 50mm
Working Pressure	:	4 ~ 7 Bar

MP 635

Features

- Rubber comfort grip ensures a non slip handling
- Rugged and long lasting one piece steel driver blade
- No – mar tip avoids marking on soft wood
- Pro gasket with metal inside
- Light weight and easy loading

Used for

- Frame, Upholstery, Furniture, Shoe Making, Decorative Trimming, Modular Kitchen, Drawer Guide & Glazing and Beading etc.

23 Gauge

Shank Dia	:	0.64mm
Leg Length	:	12~35mm

Tools Specifications

Pin Use	:	23 gauge
Leg Length	:	12 ~ 35mm
Working Pressure	:	4 ~ 7 Bar

MCN 57

Features

- Rubber comfort grip ensures a non slip handling and reduces vibrations and fatigue
- Body in high strength aluminum alloy for a good balance and ease of handling
- High impact engineered plastic magazine with adjustable bottom steel plate
- Multi directional exhaust cover
- Touch strike security system
- Metal guard to protect tool body

Used for

- Decking, Siding, Cable Reels, Pallets, Furniture, Fencing, Boxes & Crates & Crating and Sheathing etc.

15° Coil Nails



Tools Specifications

Coil Use	:	15° wire weld
Shank Dia	:	2.1 ~ 2.3mm
Nail Head	:	5.0 ~ 5.7mm
Nail Length	:	25 ~ 57mm
Working Pressure	:	5 ~ 7 Bar

MCN 70

Features

- Rubber comfort grip ensures a non slip handling and reduces vibrations and fatigue
- Body in high strength aluminum alloy for a good balance and ease of handling
- High impact engineered plastic magazine with adjustable bottom steel plate
- Touch strike security system
- Metal guard to protect tool body

Used for

- Decking, Siding, Cable Reels, Pallets, Furniture, Fencing, Boxes & Crates & Crating and Sheathing etc.

15° Coil Nails



Tools Specifications

Coil Use	:	15° wire weld
Shank Dia	:	2.3 ~ 2.9mm
Nail Head	:	5.0 ~ 7.0mm
Nail Length	:	45 ~ 70mm
Working Pressure	:	5 ~ 7 Bar

MI CN-70

Features

- Rubber comfort grip ensures a non slip handling and reduces vibrations and fatigue
- Body in high strength aluminum alloy for a good balance and ease of handling
- High impact engineered nylon magazine with adjustable bottom steel plate
- Touch strike security system
- Metal guard to protect tool body

Used for

- Decking, Siding, Cable Reels, Pallets, Furniture, Fencing, Boxes & Crates & Crating and Sheathing etc.

15° Coil Nails



Tools Specifications

Coil Use	:	15° wire weld
Shank Dia	:	2.3 ~ 2.9mm
Nail Head	:	5.0 ~ 7.0mm
Nail Length	:	45 ~ 70mm
Working Pressure	:	5 ~ 7 Bar

MCN 90

Features

- Rubber comfort grip ensures a non slip handling and reduces vibrations and fatigue
- Body in high strength aluminum alloy for a good balance and ease of handling
- High impact engineered plastic magazine with adjustable bottom steel plate
- Multi directional exhaust cover
- Touch strike security system
- Metal guard to protect tool body

Used for

- Decking, Siding, Cable Reels, Pallets, Furniture, Fencing, Boxes & Crates & Crating and Sheathing etc.

15° Coil Nails



Tools Specifications

Coil Use	:	15° wire weld
Shank Dia	:	2.5 ~ 3.33mm
Nail Head	:	6.0 ~ 7.0mm
Nail Length	:	50 ~ 90mm
Working Pressure	:	5 ~ 8 Bar

MI CN-90

Features

- Rubber comfort grip ensures a non slip handling and reduces vibrations and fatigue
- Body in high strength aluminum alloy for a good balance and ease of handling
- High impact engineered nylon magazine with adjustable bottom steel plate
- Multi directional exhaust cover
- Touch strike security system

Used for

- Decking, Siding, Cable Reels, Pallets, Furniture, Fencing, Boxes & Crates & Crating and Sheathing etc.

15° Coil Nails



Tools Specifications

Coil Use	:	15° wire weld
Shank Dia	:	2.5 ~ 3.33mm
Nail Head	:	6.0 ~ 7.0mm
Nail Length	:	50 ~ 90mm
Working Pressure	:	5 ~ 8 Bar

MCN 100

Features

- Very powerful tool, able to countersink nails into hard wood
- Rubber comfort grip ensures a non slip handling and reduces vibrations and fatigue
- Body in high strength aluminum alloy for a good balance and ease of handling
- High impact engineered plastic magazine with adjustable bottom steel plate
- Downwards directional exhaust
- Built - in silencer to reduce exhaust noise level
- Touch strike security system
- Metal guard to protect tool body

Used for

- Decking, Siding, Cable Reels, Pallets, Furniture, Fencing, Boxes & Crates & Crating and Sheathing etc.

15° Coil Nails



Tools Specifications

Coil Use	:	15° wire weld
Shank Dia	:	2.5 ~ 3.33mm
Nail Head	:	6.5 ~ 7.5mm
Nail Length	:	65 ~ 100mm
Working Pressure	:	5 ~ 8 Bar

MIE 80-16E

No Need of
- Air Compressor
- Lubrication
- Long Hoses
- Adapters

Features
- Light weight tool
- Easy to carry for on site working
- One hand latch for quick reloading

Used for
- Beading, Frame, Iron boards, Canvas, Upholstery & Leather etc.

PLUG & PLAY ELECTRIC TACKER

Head Dia	:	2.00mm (Brads)
Thickness	:	1.00 x 1.25mm
Leg Length	:	10~50mm



Outer Crown	:	12.80mm
Inner Crown	:	11.50mm
Thickness	:	0.60 x 0.90mm
Leg Length	:	3~16mm

Tools Specifications

Staple Use	:	No.80, 18 Gauge (Brads)
Leg Length	:	6 ~ 16mm (Brads 15mm)
Speed	:	30 Shots / minutes
Power required	:	AC 220-240V, 50Hz
Power Rated	:	600 Watts

ISR 34

Features
- Robust metal construction
- Easily lifts heavy duty staples
- In built clamping avoids staples kick back
- Ergonomically designed plastic handle to ensure the safety of knuckles of users hand during operation

Tools Specifications

Length	:	177 mm
Remove Staples	:	Heavy Duty*

* Remove one staple at a time

Staples	Outer Crown	Inner Crown	Wire Dimension	Leg Length
24 Series	12.80mm	11.90mm	0.35 x 0.70mm	6~8mm
23 Series	13.00mm	11.60mm	0.60 x 0.75mm	6~24mm
T Series	12.75mm	11.60mm	0.51 x 0.70mm	8~13mm
No. 4	10.50mm	09.40mm	0.57 x 1.20mm	6~14mm
No. 7C	09.00mm	07.70mm	0.60 x 0.75mm	6~12mm
No. 80	12.80mm	11.50mm	0.60 x 0.90mm	3~16mm
No. 10F	11.30mm	10.10mm	0.52 x 0.70mm	2.5~16mm
No. 10J	11.20mm	10.00mm	0.60 x 1.20mm	6~16mm
No. 90	05.60mm	03.40mm	0.95 x 1.20mm	9~40mm
No. 100	10.80mm	07.80mm	1.40 x 1.60mm	25~50mm
No. P25 / 16WC	25.00mm	22.00mm	1.40 x 1.60mm	16~38mm
No. 35	35.00mm	33.00mm	0.90 x 2.30mm	15~22mm

Brads Nails	Gauge	Head Dia	Wire Dimension	Leg Length
T Series	16	2.80mm	1.40 x 1.60mm	25~64mm
F Series	18	2.00mm	1.00 x 1.25mm	10~50mm

Coil Nails	Shank Dia	Alignment	Head Dia	Leg Length
Wire Weld	2.1~2.9mm	15°~16°	5~7mm	32~90mm

C Ring	Outer Crown	Wire Size	Leg Length
Copper / Zinc Coating	24.00mm	1.80mm	12.5mm

24 Series



Available sizes
6 & 8mm

23 Series



Available sizes
6, 8, 10, 13, 15,
17, 20 & 24mm

T Series



Available sizes
8, 10 & 13mm

No. 4



Available sizes
6, 8, 10, 12 & 14 mm

No. 14

Up to 6.5 mm(1/4")
Round Wire

No. 15



Up to 4.0 mm(5/32 ")
Flat or Round Cable

No. 7C



Available sizes
6, 8, 10 & 12mm

No. 80



Available sizes
3, 3.5, 3.75, 4, 6, 8,
9, 10, 12, 14 & 16mm

No. 10 F



Available sizes
2.5, 3, 3.5, 4, 6,
8, 10, 12, 14 & 16mm

No. 10 J



Available sizes
6, 8, 10 & 12mm

No. 90



Available sizes
9, 12, 16, 18, 22,
25, 30, 35 & 40mm

No. 100



Available sizes
25, 30, 35, 38,
40, 44 & 50mm

No. P25 / 16WC



Available sizes
16, 22, 25,
30, 35 & 38mm

No. 35



Available sizes
15,18, 20 & 22mm

T Series

16 Gauge Brads

Available sizes
25, 32, 38, 45, 50 & 64mm

F Series

18 Gauge Brads

Available sizes
10, 12, 15, 16, 20,
25, 30, 32, 40 & 50mm

15° Coil Nails



Available sizes	
Shank Dia	Shank Length
2.1	25, 30, 32, 38 & 45mm
2.3	45 & 50mm
2.5	50, 57, 60 & 65mm
2.8 / 2.9	70, 75 & 90mm
3.0	100mm
3.2	100mm
3.5	125mm

C / Hog Ring

24 Series (Copper / Zinc)



Available size
24mm

MiLES

a tool for every hand...™

munix™

FASTENING TOOLS

- ☐ MANUAL
- ☐ PNEUMATIC
- ☐ ELECTRIC
- ☐ HAMMER
- ☐ STAPLES
- ☐ NAILS
- ☐ C-RINGS

KANGARO INDUSTRIES (REGD.)
KANIN (INDIA)
KANGARO INDUSTRIES LTD.
(An ISO 9001 & 14001 company)
MUNIX (INDIA) PVT. LTD.

B-XXX-6754, Focal Point,
Ludhiana - 141 010 (INDIA)
Tel : (+91) 161-2679000 (30 Lines)
Fax: (+91) 161-2674903, 2672158
E.Mail : sales@milesincorporation.com
Internet : www.milesincorporation.com

DEALERS / DISTRIBUTORS ADDRESS:

kangaro, munix and MiLES of Kangaro Industries (Regd.)

* The colours shown in catalogue are indicative & may vary from actual and the specifications of our products are subject to change without prior notice because of our continuous efforts to improve the quality.

08/14